

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A method of dynamic re-configurable speech recognition comprising:

determining parameters of a background model and a transducer model at a periodic time during a received voice request;

determining an adapted speech recognition model based on the background model and the transducer model;

determining information in the voice request based on the adapted speech recognition model; and

increasing the periodic time when successive changes in sampled noise information [[or]] and sampled transducer information do not exceed a threshold value.

2. (Canceled)

3. (Previously Presented) The method of claim 1, wherein,

the parameters of the background model are determined based on a first sample period; and

the parameters of the transducer model are determined based on a second sample period.

4. (Previously Presented) The method of claim 1, further comprising:

saving at least one of the parameters of the background model or the parameters of the transducer model.

5. (Currently Amended) A system for dynamic re-configurable speech recognition comprising:

a background model estimation circuit for determining a background model during a voice request based on estimated background parameters determined at a periodic time during a reception of the voice request;

a transducer model estimation circuit for determining a transducer model of the voice request based on estimated transducer parameters determined at the periodic time during a reception of the voice request;

an adaptation circuit for determining an adapted speech recognition model based on a speech recognition model, the background model and the transducer model; and

a controller adapted to increase the periodic time when successive changes in sampled noise information [[or]] and sampled transducer information do not exceed a threshold value.

6. (Previously Presented) The system of claim 5, wherein, the controller periodically activates the background model estimation circuit and the transducer model estimation circuit.

7. (Original) The system of claim 6, wherein,
the background model is determined based on a first sample period; and
the transducer model is determined based on a second sample period.

8. (Previously Presented) The system of claim 6, wherein the controller saves at least one of the background model or the transducer model into storage.

9-12. (Canceled)

13. (Currently Amended) A tangible computer readable storage medium comprising:
computer readable program code embodied on a tangible computer readable storage medium, said computer readable program code usable to program a computer to perform a method for dynamic re-configurable speech recognition comprising:

determining parameters of a background model and a transducer model at a periodic time during a received voice request;

determining an adapted speech recognition model based on the background model and the transducer model;

determining information in the voice request based on the adapted speech recognition model; and

increasing the periodic time when successive changes in sampled noise information [[or]] and sampled transducer information do not exceed a threshold value.

14. (Currently Amended) A method of dynamic re-configurable speech recognition comprising:

periodically determining user specific parameters of a background model and a transducer model at periodic time periods during a received voice request;

determining an adapted speech recognition model based on the background model and the transducer model;

determining information in the voice request based on the adapted speech recognition model; and

increasing the periodic time when successive changes in the user specific parameters of the background model [[or]] and the transducer model do not exceed a threshold value.

15. (Canceled)

16. (Previously Presented) The method of claim 1, wherein determining parameters of a background model and a transducer model at a periodic time during a received voice request further comprises periodic sampling during periods of speech inactivity while receiving the voice request.

17-20. (Canceled)

21. (Previously Presented) The method of claim 1, further comprising:
dynamically determining the periodic time based, at least in part, on a frequency or a magnitude of determined changes in the sampled noise information.

22-23. (Canceled)

24. (Previously Presented) The system of claim 5, wherein the controller is further adapted to adjust the periodic time based, at least in part, on a frequency or a magnitude of determined changes in successively sampled ones of the noise information.

25. (New) The tangible computer readable storage medium of claim 13, wherein:
the background model is determined based on a first sample period; and
the transducer model is determined based on a second sample period.

26. (New) The tangible computer readable storage medium of claim 13, wherein the method further comprises saving at least one of the background model or the transducer model.

27. (New) The tangible computer readable storage medium of claim 13, wherein determining parameters of the background model and a transducer model at a periodic time during a received voice request further comprises periodic sampling during periods of speech inactivity while receiving the voice request.

28. (New) The tangible computer readable storage medium of claim 13, wherein the method further comprises dynamically determining the periodic time based, at least in part, on a frequency or a magnitude of determined changes in the sampled noise information.